



The Onkyo "All-There" Component System That Gives You Extra Value

As simple as the concept behind this Onkyo Audio System may appear, as hard is it to realize: to give you the greatest possible listening enjoyment and the greatest possible technological value at the smallest possible expense and with the least complexity. On the value side, there's a high fidelity grade FM/AM stereo receiver with more power than you'll need for a houseful of fine music; with latest technology including FET, PLL, microphone mixing, two tuning meters and other assets that, we admit, may sound a little mysterious at first but that, you will admit, make a great contribution to better sound quality. On the value side, there is also an automatic turntable with precision belt drive and diamond-tipped hi-fi cartridge. Still on the value side, there's a pair of 2-way bass reflex speakers for overpowering bass and sizzling highs. Even fourchannel sound can be yours, with the simple addition of another speaker pair to the Y-7000's speaker matrix. And the complexity? Onkyo engineers have untied all the knots by pre-matching all components for optimum sound performance. The Onkyo Y-7000. A superlative sound package at superlative savings.



The Onkyo Y-7000 A superlative sound package

The Receiver

A houseful of sound power

Delivering a total of 40 watts of sound power, this Onkyo receiver can more than fill a large living room with vibrant, lifelike music.

Circuit engineering true to Onkyo excellence

The tuner section assures optimum FM, FM stereo and AM reception, thanks to its advanced engineering with 6-element (FM) ceramic filters and PLL (phase locked loop) FM stereo decoding. Two tuning meters — a signal strength meter for FM and AM and a center-channel meter for FM only — make quick, precise tuning a cinch. The FM front end features a field effect transistor for high sensitivity and distortion-free reception.

Microphone mixing puts you centerstage


Plug in a microphone, and you're the star — sing or play along with your favorite recording artists on records, FM or tape.

Tape monitor switch for error-free tape recordings

A stereo tape deck — cassette, open reel or cartridge — can be connected to the pin jacks or the DIN-type REC/PB connector. If the deck has monitor provisions, you can check the actual recording quality with Y-7000's monitor switch.

Stereo now, four-channel tomorrow

Add another pair of speakers (optional), and you're smack in the middle of a 4-channel ambient sound field. The built-in speaker matrix circuit of the Y-7000 enhances any (stereo or quad) program with concert-hall-like "surround sound" atmosphere.







e at superlative savings

The Turntable

Fully automatic tonearm return

At the end of the record, the tonearm returns to its rest position automatically. You can also interrupt a record midway by simply pushing the Auto Cut lever.

Precision belt drive

A synchronous motor of exceptionally good speed stability drives the large aluminum diecast platter via an accurately machined belt, giving you sound free of vibrations or rumble.

Hi-fi grade tonearm with lifter

The tonearm, a low-mass pipe arm, can be raised and lowered very gently with its oil-damped lifter, for maximum record protection. It also features a directly readable tracking force adjustment to accommodate phono cartridges other than the supplied one.



Diamond-tipped stereo cartridge

To bring out the best in your records, Onkyo equips this turntable with a magnetic stereo cartridge of high compliance and sharp stereo channel separation. The diamond stylus tracks the grooves accurately and has a service life of at least 1000 LP sides.

The Speakers

2-way system with 16cm ($6\frac{1}{2}$ '') woofer and 5cm (2'') tweeter

Sharply defined, transparent sound of surprising sonority is yours with these Onkyo 2-way speaker systems.



Thanks to the bass reflex enclosure, bass sound remains powerful and natural down into the ultra low frequency range.

The Total System

Attractive simulated rosewood exterior

Surfaces are finished in rosewood grained synthetics that blend into modern as well as classical room decors. The four units are easy to place on shelves or sideboards for easy operation and minimum space requirements.



NKYOR

Simply Add 2 Speakers for 4-Channel "Speaker Matrix" Realism



Specifications

Receiver section

Tuning Range

Sensitivity

Power Output Dynamic: Semiconductors

Power Supply Rating

Controls

Outputs

Inputs

MIC VOLUME. TUNING, SELECTOR (AM, FM AUTO,

FM: 88-108MHz

40 watts total

21 Transistors

V 50/60Hz

TREBLE

1 FET

17 Diodes, 3 ICs,

AC 110/120/220/240

POWER, VOLUME,

BALANCE, BASS,

AM: 530-1605kHz

AM: 40µV (S/N 20dB)

PHONO) TAPE MONITOR,

LOUDNESS SPEAKER (FRONT,

BACK)

HEADPHONES TAPE REC OUT DIN REC OUT **PHONO** TAPE PLAY

DIN PLAY MIC

FM/AM ANTENNA FM: 300Ω balanced Antennas

outer terminal FM: 3µV (S/N 30dB)

Turntable section

Type

autocut and lifter Turntable Platter diecast, belt driven Static balance pipe Tonearm

arm with detachable headshell and direct reading tracking force

Cartridge Frequency Response Impedance

Compliance Output Separation Stylus Tip

Tracking force Motor Speaker section

Type Speaker Components

Impedance Frequency Response 50-20,000Hz

Features stereo system

AM: Built in ferrite core antenna and

2-speed autoplayer with autoreturn.

30cm (12") aluminum

0C-35V VM type

20-20,000Hz 47k

7 x 10-6cm/dyne 3.5mV

20dB DN-35 ST 0.65 mil (16.5µ) Diamond

4-pole synchronous

2-way bass reflex type 16cm (6½") woofer and 5cm mid-tweeter

8 ohms 4-unit AM/FM

quasi-complementary SEPP OTL Mic mixing circuit PLL MPX circuit 2 tuning meters Ceramic filters for FM IF and AM IF stage Tape monitor circuit Speaker matrix 4-channel circuit Belt driven turntable Arm lifter VM cartridge Receiver section 458 (18 1/16'')W x 151 (5 15/16")H x

All silicon transistor

388mm (15 5/16")D Speaker section 265 (10 7/16")W x 485 (19 1/8'')H x 217mm (8 7/16")D Turntable section 458 (18 1/16")W x 164 (6 1/2'')H x 360mm (14 3/16'')D Receiver section 6.5 kg (14'.3 lbs)

Speaker section 3.8 kg (8.4 lbs) each Turntable section 8.2 kg (18 lbs)

Specifications and design are subject to change without notice.

Dimensions

Weight

Added Enjoyment

"S-1000" is the model number to remember for

the extra pair of speakers (optional) needed for 4-channel enjoyment. Connect them to the speaker matrix outputs, and you're in the center of dynamic wrap-around sound. Each unit contains a 16cm (61/2") woofer and

Stereo music for you and you alone...with our hi fi headset. Soft ear pads for greatest comfort, 5-meter (15ft.) spiral cord for unrestricted freedom of movement. 18 22,000Hz. Model PH-747.

Private Headphone Listening

Microphone Mixing

For sing-along, play-along fun. High grade dynamic microphone with highly sensitive magnet structure picks up the faintest whisper. Wind screen eliminates noise when used outdoors. Cardioid directionality. With 5m (15ft.) cable and microphone stand.







ONKYO CORPORATION

International Division: No. 24 Mori Bldg., 23-5, 3-chome, Nishi-shinbashi, Minato-ku, Tokyo, Japan. Telex 242-3551 ONKYO J Tel. 03-432-6981

ONKYO U.S.A. CORPORATION

5cm (2") tweeter.

Four-Channel Sound

Midwest Office: 25-19 43rd Avenue, Long Island City, New York 11101, U.S.A. Tel. (212) 729-2323 Midwest Office. 935 Sivert Drive, Wood Dale, Illinois 60191, U.S.A. Tel. (312) 595-2970

ONKYO-DEUTSCHLAND GMBH ELECTRONICS 8034 München-Germering, Industriestraße 18, West Germany Telex 05-21726 Tel. (089) 84 50 41 ONKYO AG CH-8306 Brüttisellen bei Zürich, Dorfstraße 13, Switzerland Telex 5-7984 Tel. 01-8330674

ONKYO HANDELSGESELLSCHAFT MBH A-5020 Salzburg, Griesgasse 4/II; Austria Telex 6-3539 Tel. 43462

