





Car Audio Amplifiers

The qualities that put McIntosh home products in a class by themselves are built into every McIntosh Car Audio product. Accurate and transparent reproduction, plus crank-it-up performance that beats anything on the road today.

Power Output*	Power Band	THD** 4 ohm Normal Mode	Head-Room	Frequency Response	Input Sensitivity	A-Wtd. S/N	DC Input Voltage	Current Consumption	Dimensions (HxWxD) Weight
 <p>MCC204 4ch: 50W (4ohm) or 100W (2ohm) x 4 3 ch: 50W x 2, 200W x 1 (4ohm) 2 ch: 200W x 2 (4ohm)</p>	20Hz to 20kHz	0.005%	1.0dB	20Hz to 20kHz, +0/-0.25dB 10Hz to 100kHz, +0/-3.0dB	0.5V To 8V	105dB (1.5V)	12.0V	Idle: 2.5A Rated Power: 40A (4ohms)	Inches: 3 x 12.5 x 13.7 cm: 7.6 x 31.8 x 34.8 19 lbs. (8.6kg)
 <p>MCC301M 1 ch: 300W (4ohm) or 600W (2ohm)</p>	20Hz to 20kHz	0.005%	1.0dB	20Hz to 20kHz, +0/-0.25dB 10Hz to 100kHz, +0/-3.0dB	0.5V To 8V	105dB (1.5V)	12.0V	Idle: 2.5A Rated Power: 45A (4ohms) 100A (2ohms)	Inch: 3.0 x 12.5 x 13.7 cm: 7.6 x 31.8 x 34.8 14.5 lbs. (6.6kg)
 <p>MCC302 2 ch: 150W (4ohm) or 300W (2ohm) 1 ch: 600W (4ohm)</p>	20Hz to 20kHz	0.005%	1.0dB	20Hz to 20kHz, +0/-0.25dB 10Hz to 100kHz, +0/-3.0dB	0.5V to 8V	105dB (1.5V)	12.0V	Idle: 2.5A Rated Power: 50A (4ohms)	Inch: 3.0 x 12.5 x 13.7 cm: 7.6 x 31.8 x 34.8 14.5 lbs. (6.6kg)
 <p>MCC404 4 ch: 100W (4ohm) 3 ch: 100W x 2, 400W x 1 (4ohm) 2 ch: 400W x 2 (4ohm)</p>	20Hz to 20kHz	0.005%	1.0dB	20Hz to 20kHz, +0/-0.25dB 10Hz to 100kHz, +0/-0.3dB	0.5V To 8V	105dB (1.5V)	12.0V	Idle: 3.5A Rated Power: 70A (40)	Inch: 3.0 x 12.5 x 18.4 cm: 7.6 x 31.8 x 46.7 20.2 lbs. (9.2kg)
 <p>MCC404M 4 ch: 100W (4ohm) 3ch: 100W x 2, 400W x 1 (4ohm) 2 ch: 400W x 2 (4 ohm)</p>	20Hz to 20kHz	0.005%	1.0dB	20Hz to 20kHz, +0/-0.25dB 10Hz to 100kHz, +0/-3.0dB	0.5V To 8V	105dB (1.5V)	12.0V	Idle: 3.5A Rated Power: 70A (40)	Inch: 3.0 x 12.5 x 18.4 cm: 7.6 x 31.8 x 46.7 20.2 lbs. (9.2kg)
 <p>MCC406M 6 ch: 50W x 4, 100W x 2 (4ohm) 5 ch: 50W x 4, 400W x 1 (4ohm) 4 ch: 200W x 2, 100W x 2 (4ohm) 3 ch: 200W x 2, 400W 1 (4ohm)</p>	20Hz to 20kHz	0.005%	1.0dB	20Hz to 20kHz, +0/-0.25dB 10Hz to 100kHz, +0/-3.0dB	0.5V To 8V	105dB (1.5V)	12.0V	Idle: 3.5A Rated Power: 70A (40)	Inch: 3.0 x 12.5 x 18.4 cm: 7.6 x 31.8 x 46.7 20.5 lbs. (9.3kg)
 <p>MCC602TM 2 ch: 300W (8.4.2ohm) 1 ch: 600W (4/2/1ohm)</p>	20Hz to 20kHz	0.005%	1.0dB	20Hz to 20kHz, +0/-0.25dB 10Hz to 100kHz, +0/-3.0dB	1V To 8V	114dB (2V)	12.0V	Idle: 3.5A Rated Power: 70A (40)	Inch: 4.2 x 12.5 x 26.9 cm: 10.7 x 31.8 x 68.3 50.0 lbs. (23kg)

* Power Output: Minimum sine wave continuous average power output per channel from 20Hz to 20kHz with all channels operating.

** Total Harmonic Distortion: 0.005% max at any level from 250 milliwatts to rated power output.

For more information on McIntosh Car Audio and other McIntosh equipment contact your nearest Authorized McIntosh Dealer!

