



CAR AMPLIFIER COMPARISON CHART

Model	Power Output*	Power Band	THD** at 4 ohms normal mode	Head-room	Frequency Response	Input Sensitivity	A-Weighted S/N Ratio	DC Input Voltage	Current Consumpt.	Overall Dimensions HxWxD	Weight (each)
MC301M	1 Channel: 300W at 4 ohms or 600W at 2 ohms	20Hz to 20kHz	0.005%	1.0dB	20Hz to 20kHz, +0 / -0.25dB; 10Hz to 100kHz, +0 / -3.0dB	0.5V to 8V	105dB (1.5V)	12.0V	Idle: 2.5A Rated power: 45A (4 ohms) 100A (2 ohms)	3 x 12.5 x 13.7	14.5 lbs. net; 17 lbs. boxed
MMCC302	2 Channel: 150W at 4 ohms or 300W at 2 ohms; 1 Channel: 600W at 4 ohms	20Hz to 20kHz	0.005%	1.0dB	20Hz to 20kHz, +0 / -0.25dB; 10Hz to 100kHz, +0 / -3.0dB	0.5V to 8V	105dB (1.5V)	12.0V	Idle: 2.5A Rated power: 50A (4 ohms)	3 x 12.5 x 13.7	14.5 lbs. net; 17 lbs. boxed
MCC602TM	2 Channel: 300W 8/4/2 ohms; 1 Channel: 600W 4/2/1 ohm	20Hz to 20kHz	0.005%	1.0dB	20Hz to 20kHz, +0 / -0.25dB; 10Hz to 100kHz, +0 / -3.0dB	1V to 8V	114dB (2V)	12.0V	Idle: 3.5A Rated power: 100A	4.2 x 12.5 x 26.9	50.5 lbs. net; 58.5 lbs. boxed
MCC204	4 Channel: 50W at 4 ohms or 100W at 2 ohms x 4; 3 Channel: 50W x 2, 200W x 1 at 4 ohms; 2 Channel: 200W x 2 at 4 ohms	20Hz to 20kHz	0.005%	10dB	20Hz to 20kHz, +0 / -0.25dB; 10Hz to 100kHz, +0 / -3.0dB	0.5V to 8V	105dB (1.5V)	12.0V	Idle: 2.5A Rated power 40A (4 ohms)	3 x 12.5 x 13.7	14.5 lbs. net; 17 lbs. boxed
MCC404	4 Channel: 100W at 4 ohms; 3 Channels: 100W x 2, 400W x 1 at 4 ohms; 2 Channels 400W x 2 at 4 ohms.	20Hz to 20kHz	0.005%	1.0dB	20Hz to 20kHz, +0 / -0.25dB; 10Hz to 100kHz, +0 / -3.0dB	0.5V to 8V	105dB (1.5V)	12.0V	Idle: 3.5A Rated power: 70A (4 ohms)	3 x 12.5 x 18.4	20.2 lbs. net; 23.2 lbs. boxed
MCC404M	4 Channel: 100W at 4 ohms; 3 Channels: 100W x 2, 400W x 1 at 4 ohms; 2 Channel: 400W x 2 at 4 ohms	20Hz to 20kHz	0.005%	1.0dB	20Hz to 20kHz, +0 / -0.25dB; 10Hz to 100kHz, +0 / -3.0dB	0.5V to 8V	105dB (1.5V)	12.0V	Idle: 3.5A Rated power: 70A (4 ohms)	3 x 12.5 x 18.4	20.2 lbs. net; 23.2 lbs. boxed
MCC406M	6 Channel: 50W x 4, 100W x 2 at 4 ohms, 5 Channel: 50W x 4, 400W x 1 at 4 ohms; 4 Channel: 200W x 2, 100W x 2 at 4 ohms; 3 Channel: 200W x 2, 400W x 1 at 4 ohms	20Hz to 20kHz	0.005%	1.0dB	20Hz to 20kHz, +0 / -0.25dB; 10Hz to 100kHz, +0 / -3.0dB	0.5V to 8V	105dB (1.5V)	12.0V	Idle: 3.5A Rated power: 70A (4 ohms)	3 x 12.5 x 18.4	20.5 lbs. net; 23.5 lbs. boxed

* Power Output: Minimum sine wave continuous average power output per channel from 20Hz to 20kHz with all channels operating.

**Total Harmonic Distortion: 0.005% max at any level from 250 milliwatts to rated power output.