

# SOURCE COMPARISON CHART

Feature	MR85 AM/FM Tuner	MVP861 Audio Video Player	MS300 Music Server	MCD205 Five Disc CD Player	MDA1000 Ballanced Upsampling D-To A Converter	MCD1000 CD/CDR/CDR-W Transport
Number of Channels	Two, Stereo	Two, Stereo & 5.1 Audio/Video	Two, Stereo, Audio/Video	Two, Stereo	Two, Stereo	Digital PCM out
Frequency Response	20 to15,000 Hz +0, - 1 dB	4Hz to 100kHz	4Hz to 20kHz	5Hz to 20kHz	4Hz to 45kHz	Digital PCM out
Distortion	Stereo, 0.45% Mono, 0.3%	0.002%	0.003%	0.002%	0.002%	N/A
Signal-to-Noise Ratio	Mono: 75dB Stereo: 70dB	115dB, A-weighted	100dB A-weighted	108dB, A weighted	110dB, A weighted	N/A
D/A Conversion Type	N/A analog	Three, 192kHz/24-bit PCM/DSD Stereo DACs	24/96 Stereo A to D and D to A	24/96 Stereo, Balanced D/A converters	24/ 768 stereo using 8 D/A, Fully Balanced	Digital PCM out
Up-Sampling	N/A analog	None	None	None	768kHz all inputs	NA
Audio Output Types	Stereo Fixed, Stereo Variable	Stereo Balanced and Unbalanced, 5.1, Coaxial and Optical Digital	Stereo RCA- AnalogToslink digital Co-Ax digital	Stereo Fixed balanced and unbalanced	Stereo Fixed or Variable balanced / unbalanced	Digital PCM out
Video Output Types	N/A analog	Component, Progressive Scan, S and Composite	Component Progressive Scan, S, Composit	Music Only	Music Only	Digital PCM out
Software Decoded	AM/ FM Broadcast	SACD, DVD-A, DVD-V, CD, DVD+/-RW, Audio CD-R/RW, MP3, CDR/RW, JPEG Photo, Kodak Picture CD and Fujicolor CD.	CD, CD-R/CD-RW, MP3, all data rates FLAC Lossless	Redbook Two Channel CD	PCM, 32 to 96 kHz 16 to 24 bits. All data upsampled to 768 kHz.	CD, CD-R, CDR-W
Special Features	Second TM-1 Tuner may be added for two zone operation	12 bit 108 MHz Video, RS232 Port, Bass Management	300 GB hard drive holds over 850 CDs lossless	Single or 5 CD playback. R-Core type Power Supply	Fully Ballanced including Twin R Core Power Supplies	Silent Aluminum Sheet CD drawer R-Core Power Supply
Fiber-Optic Glass Panel	Lightbulbs	Yes	Yes	Lightbulbs	Yes, New 3D style	Yes, New 3D style
Remote Control	Yes by McIntosh Control Center Data	Yes	Yes, Handheld IR, keyboard, ethernet	Yes, Handheld IR or Data	Yes, Handheld IR or Data	Yes, Handheld IR or Data
Third Party Control	Control Center Data	RS232, IR input jack	ethernet, RS232	RS232, IR input jack	IR input jack	IR input Jack
Dimensions	17-1/2" W, 5-3/8" H, 17-1/2" D	17-1/2" W, 5-3/8" H, 15" D	17-1/2" W, 5-3/8" H, 15" D	17-1/2" W, 5-3/8" H, 15" D	17-1/2 W, 5-3/8 H, 16-1/8" D	17-1/2" W, 6" H, 16-1/8" D
Weight	25.5 lbs. Net, 43 lbs. Shipping	22 lbs. Net, 36 lbs. Shipping	22 lbs. Net, 36 lbs. Shipping	21 lbs. Net, 35 lbs. Shipping	24 lbs. Net, 38 lbs. shipping	27.5 lbs. Net, 41.5 lbs. shipping